



Modular Wetland System O & M
(Media Filter & Wetland/Bioretention)

Maintenance Overview –

A. Every installed MWS – Linear unit is to be maintained by the Supplier, or a Supplier approved contractor. The cost of this service varies among providers.

B. The MWS – Linear is a multi-stage self-contained treatment train for stormwater treatment. Each stage protects subsequent stages from clogging. Stages include: screening, separation, cartridge media filtration, and biofiltration. The biofiltration media works with or without plants as the microorganisms play the primary biological removal role.

1. Clean Separation (sediment) Chamber – separation occurs in the pre-treatment chamber located at the influent end of the system. This chamber has a large capacity for trash, debris and sediments. This chamber targets TSS, and particulate metals and nutrients. This procedure can be performed with a standard vacuum truck. This chamber is located directly under the manhole or grate access cover.

2. Replace Cartridge Filter Media – Primary filtration is provided by a horizontal flow cartridge filter utilizing coarse granular media. Each cartridge has a media surface area of 25 square feet. The large surface area will insure long term operation without clogging. The cartridge filter targets fine TSS, metals, nutrients, hydrocarbons, turbidity and bacteria. Media life depends on local loading conditions and can easily be replaced and disposed of without any equipment. The filters are located in the pre-treatment chamber. Entry into chamber required to replace granular media. Each cartridge contains 8 filter columns.

3. Evaluate Wetland Media Flow Hydraulic Conductivity – The systems flow can be assessed from the discharge chamber. This should be done during a rain event. By viewing into the discharge chamber the flow out of the system can be observed. If little to no flow is observed from the lower valve or orifice plate this is a sign of potential wetland media (biofiltration) maintenance needs.

4. Wetland Media Replacement – biofiltration is provided by an advance horizontal flow vegetated wetland. This natural filter contains a mix of sorptive media that supports abundant plant life. This biofilter targets the finest TSS, dissolved nutrients, dissolved metals, organics, pesticides, oxygen demanding substances and bacteria. This filter provides the final polishing step of treatment. If prior treatment stages are properly maintained, the life of this media can be up to 20 years. Replacement of the media is simple. Removal of spent media can be done with a shovel or a vacuum truck.

C. The MWS – Linear separation chamber, cartridge filter media and wetland media are designed to allow for the use of vacuum removal of captured pollutants and spent filter media by centrifugal compressor vacuum units without causing damage to the filter or during normal cleaning and maintenance. Filter and chambers can be cleaned from finish surface through standard manhole or grate access.

Maintenance Procedures –

1. Clean Separation (sediment) Chamber – Modular Wetland Systems, Inc. recommends the **separation chamber** be inspected and cleaned a minimum of once a year. The procedure is easily done with the use of any standard vacuum truck. *This procedure takes approximately 30 minutes.*

1. Remove grate or manhole to gain access.
2. With a pressure washer spray down pollutants accumulated on walls and cartridge filters.
3. Vacuum out separation chamber and remove all accumulated debris and sediments.
4. Replace grate or manhole cover.
5. Transport all debris, trash, organics and sediments to approved facility for disposal in accordance with local and state requirements.

2. Replace Cartridge Filter Media – Modular Wetland Systems, Inc. recommends the **cartridge filters** media be inspected and cleaned a minimum of once a year. The procedure will require prior maintenance of separation chamber. *Replacement of media takes approximately 45 minutes.*

1. Remove grate or manhole to gain access.
2. Enter separation chamber.
3. Unscrew the two ½” diameter bolts holding the lid on each cartridge filter and remove lid and place outside of unit.
4. Remove each of the 8 filter cartridge cages in each cartridge.
5. Spray down the outside and inside of the cartridge filter to remove any accumulated sediments.
6. Vacuum out spent media.
7. Replace cartridge cage and fill with new media.
8. Replace the lid and tighten down bolts.
9. Replace grate or manhole cover.
10. Transport all debris, trash, organics, spent media and sediments to approved facility for disposal in accordance with local and state requirements.

3. Evaluate Wetland Media Flow Hydraulic Conductivity – Modular Wetland Systems, Inc. recommends system flow be inspected and observed a minimum of once a year. This needs to be done during a rain event. *Inspection and Observation takes approximately 5 minutes.*

1. Open hatch of discharge chamber
2. Observe the level of flow from the bottom valve or orifice plate.
3. If flow is steady and high the system is operating normally.
4. If little or no flow is observed exiting the valve possible maintenance to the biofiltration wetland chamber may be needed. Contact Modular Wetlands for further assistance.
5. Exit chamber, close and lock down the hatch.

4. Wetland Media Replacement – Modular Wetland Systems, Inc. recommends the wetland media be replaced a minimum of one every 20 years. *Inspection takes*

approximately 15 minutes. Replacement of rock media takes approximately 6 hours and requires a vacuum truck.

1. Use a vacuum truck or shovel to remove all wetland media.
2. Spray down the walls and floor of the chamber and vacuum out any accumulated pollutants.
3. Spray down perforated piping and netting of flow matrix and the inflow and outflow end to remove any accumulated pollutants.
4. Vacuum out any standing water from the media removal and insure the chamber is cleaning.
5. Use a small backhoe to fill chamber with new media. Call Modular Wetland Systems, Inc. for media delivery information.

7. Other Maintenance Notes –

1. Following maintenance and/or inspection, the maintenance operator shall prepare a maintenance/inspection record. The record shall include any maintenance activities performed, amount and description of debris collected, and condition of the system and its various filter mechanism. .
2. The owner shall retain the maintenance/inspection record for a minimum of five years from the date of maintenance. These records shall be made available to the governing municipality for inspection upon request at any time.
3. Any person performing maintenance activities must have completed a minimum of OSHA 24-hour hazardous waste worker (hazwoper) training.
4. Remove access manhole lid or grate to gain access to filter screens and sediment chambers. Where possible the maintenance should be performed from the ground surface. Note: entry into an underground stormwater vault such as an inlet vault requires certification in confined space training.
5. Transport all debris, trash, organics and sediments to approved facility for disposal in accordance with local and state requirements.
6. The hydrocarbon boom is classified as hazardous material and will have to be picked up and disposed of as hazardous waste. Hazardous material can only be handled by a certified hazardous waste trained person (minimum 24-hour hazwoper).

Description

A wet vault is a vault with a permanent water pool, generally 3 to 5 feet deep. The vault may also have a constricted outlet that causes a temporary rise of the water level (i.e., extended detention) during each storm. This live volume generally drains within 12 to 48 hours after the end of each storm.

California Experience

There are currently several hundred stormwater treatment facilities in California that use manufactured wet vaults currently in operation in California.

Advantages

- Internal baffling and other design features such as bypasses may increase performance over traditional wet vaults and/or reduce the likelihood of resuspension and loss of sediments or floatables during high flows.
- Head loss is modest.

Limitations

- Concern about mosquito breeding in standing water
- The area served is limited by the capacity of the largest models.
- As the products come in standard sizes, the facilities will be oversized in many cases relative to the design treatment storm, increasing the cost.
- Do not remove dissolved pollutants.
- A loss of dissolved pollutants may occur as accumulated organic matter (e.g., leaves) decomposes in the units.

Design and Sizing Guidelines

Water quality volume or flow rate (depending on the particular product) is determined by local governments or sized so that 85% of the annual runoff volume is treated. There are three general configurations of wet vaults currently available, differing with the particular manufacturer.

Vault System A: This system consists of two standard precast manholes, the size varying to achieve the desired capacity. Stormwater enters the first (primary) manhole where coarse solids are removed. The stormwater flows from the first to the second (storage) manhole, carrying floatables where they are captured and retained. Further sedimentation occurs in this second manhole. The off-line serves as a storage reservoir for

Design Considerations

- Hydraulic Capacity
- Sediment Accumulation

Targeted Constituents

- ✓ Sediment
- ✓ Nutrients
- ✓ Trash
- ✓ Metals
- Bacteria
- ✓ Oil and Grease
- ✓ Organics

Removal Effectiveness

See New Development and Redevelopment Handbook-Section 5.



floatables as stormwater flows though at flow rates less than the design flow. A patented device controls the flow into the storage manhole. All flows above the stated treatment flow rate bypass through the device. The bypass prevents resuspension or loss of sediment and floatables that have accumulated in the second manhole. It is important to recognize that has storage of accumulated sediment occurs directly in the operating area of the manholes; treatment efficiency will decline over time given the reduction in treatment volume

The manufacturer currently provides 4 models, with treatment capacities (flow rate above which bypass occurs) from 2.4 to 21.8 cfs. The hydraulic capacities range from 10 to 100 cfs. As such, all stormwater achieves at least partial treatment through essentially all but the most extreme storm flows since some settling occurs in the first manhole. The manufacturer provides information on the total system (water) volume, sediment capacity, and floatable capacities. The size of the storage manhole can be varied with each of the four models to increase storage capacity as desired, following recommendations of the manufacturer. The footprint of this system ranges from about 200 to 350 ft², with heights of about 11.5 to 13.5 feet (excluding minimum soil cover and access port extenders), depending on the model. Head loss ranges from 5 to 12 inches, depending on the model. Sediment and floatable capacities range up to 201 cf and 150 gallons, respectively. The recommended point of maintenance is when about 25% of the wet pool volume is supplanted by sediment. The affect of the accumulation of sediment on performance is not given

Vault System B: This wet vault has outward appearance of a standard, rectangular wet vault, but with its own unique design for internal baffles. Included is an entrance baffle, presumably to reduce the energy of the flow entering the unit. Baffles are also affixed to the floor, purportedly to reduce resuspension of settled sediments improve performance. A floating sorbent pad may be placed near the outlet to remove free oil floating on the surface. The vault includes both a permanent wet pool, 3 feet in depth, and live storage volume that is filled during each storm. The live storage volume is accomplished by restricting the outlet. The system is modular: that is, it consists of standard units that are added to increase the length, thereby providing the desired volume. Presumably for very large sites there is a practical total length. Further capacity could be accomplished by having two or more vaults in parallel. The capacity of the system is therefore essentially unlimited, Being modular may allow the design engineer to more closely match facility size to the design event.

Vault System C: This system is like System A, but differs in two primary respects. The Stormceptor module consists of only one circular structure. Hence, standard precast manholes can be used for the smaller models but larger models are non-standard sizes. Like System A, System C has an internal bypass, involving a unique design. The purpose of the bypass is to prevent resuspension of previously suspended material. All stormwater up to the bypass rate is diverted downward into the center well where removal occurs. Flows in excess of the treatment capacity are diverted directly across the top of the device to the outlet. According to the manufacturer there is also some storage capacity for floatables immediately beneath the bypass structure.

Twelve models are available. The treatment capacity of each is not indicated for the Stormceptor as it is a function of the removal efficiency specified by the designer. The manufacturer provides a methodology for the calculation of efficiency as a function of flow rate (see Design Guidelines). Hydraulic capacities range up to approximately 63 cfs. The head requirement is a function of the model and desired hydraulic flow rate, ranging up to 21 inches.

Diameters range from 4 to 12 feet, and minimum heights up to about 13 feet plus the diameter of the incoming pipe. Sediment and floatable capacities range up to 1,470 cf and 3,055 gallons, respectively. The recommended point of maintenance is when about 15% of the wet pool volume is supplanted by sediment. The affect of the accumulation of sediment on performance is not given but can be estimated using the manufacturer's sizing methodology.

Construction/Inspection Considerations

Refer to guidelines provided by the manufacturer.

Performance

A manufactured wet vault can be expected to perform similarly to large catch basins in that its wet volume (dead storage) is similar to that determined by methodology provided in TC-20 for wet ponds. Hence, the engineer should compare the volume of the model s/he intends to select to what the volume of a constructed wet vault would be for the site. Conceivably, manufactured vaults may give better performance than standard catch basins, given the inclusion of design elements that are intended to minimize resuspension. Given this benefit, it could be argued that manufactured wet vaults can be smaller than traditional catch basins, to achieve similar performance. However, there are no data indicating the incremental benefit of the particular design elements of each manufactured product.

Siting Criteria

There are no unique siting criteria. The size of the drainage area that can be served by a manufactured wet vault is directly related to the capacities of the largest models.

Additional Design Guidelines

Refer to guidelines of the manufacturers.

Maintenance

Maintenance consists of the removal of accumulated material with an eductor truck. It may be necessary to remove and dispose the floatables separately due to the presence of petroleum product. Annual maintenance is typical.

It is important to recognize that as storage of accumulated sediment occurs directly in the operating area of the wet vault, treatment efficiency will decline over time given the reduction in treatment volume. Whether this is significant depends on the design capacity. If the total volume of the wet pool is similar to that determined by the method on TC-20, the effect on performance is minor.

Maintenance Requirements

- Each manufacturer provides storage capacities with respect to sediments and floatables, with recommendations on the frequency of cleaning as a function of the percentage of the volume in the unit that has been filled by these materials.
- The recommended frequency of cleaning differs with the manufacturer, ranging from one to two years. It is prudent to inspect the unit twice during the first wet season of operation, setting the cleaning frequency accordingly.

Cost

Manufacturers provide costs for the units including delivery. Installation costs are generally on the order of 50 to 100 % of the manufacturer's cost.

Cost Considerations

- The different geometries of the several manufactured separators suggest that when comparing the costs of these systems to each other, that local conditions (e.g., groundwater levels) may affect the relative cost-effectiveness.
- Subsurface facilities are more expensive to construct than surface facilities of similar size. However, the added cost of construction is in many developments offset by the value of continued use of the land.
- Some of the manufactured vaults may be less expensive to maintain than public domain vaults as the former may be cleaned without the need for confined space entry.
- Subsurface facilities do not require landscaping, reducing maintenance costs accordingly.

References and Sources of Additional Information

Manufacturers literature.



Design Considerations

- Tributary Area
- Area Required
- Hydraulic Head

Description

Dry extended detention ponds (a.k.a. dry ponds, extended detention basins, detention ponds, extended detention ponds) are basins whose outlets have been designed to detain the stormwater runoff from a water quality design storm for some minimum time (e.g., 48 hours) to allow particles and associated pollutants to settle. Unlike wet ponds, these facilities do not have a large permanent pool. They can also be used to provide flood control by including additional flood detention storage.

California Experience

Caltrans constructed and monitored 5 extended detention basins in southern California with design drain times of 72 hours. Four of the basins were earthen, less costly and had substantially better load reduction because of infiltration that occurred, than the concrete basin. The Caltrans study reaffirmed the flexibility and performance of this conventional technology. The small headloss and few siting constraints suggest that these devices are one of the most applicable technologies for stormwater treatment.

Advantages

- Due to the simplicity of design, extended detention basins are relatively easy and inexpensive to construct and operate.
- Extended detention basins can provide substantial capture of sediment and the toxics fraction associated with particulates.
- Widespread application with sufficient capture volume can provide significant control of channel erosion and enlargement caused by changes to flow frequency relationships resulting from the increase of impervious cover in a watershed.

Targeted Constituents

✓ Sediment	▲
✓ Nutrients	●
✓ Trash	■
✓ Metals	▲
✓ Bacteria	▲
✓ Oil and Grease	▲
✓ Organics	▲

Legend (Removal Effectiveness)

● Low	■ High
▲ Medium	



Limitations

- Limitation of the diameter of the orifice may not allow use of extended detention in watersheds of less than 5 acres (would require an orifice with a diameter of less than 0.5 inches that would be prone to clogging).
- Dry extended detention ponds have only moderate pollutant removal when compared to some other structural stormwater practices, and they are relatively ineffective at removing soluble pollutants.
- Although wet ponds can increase property values, dry ponds can actually detract from the value of a home due to the adverse aesthetics of dry, bare areas and inlet and outlet structures.

Design and Sizing Guidelines

- Capture volume determined by local requirements or sized to treat 85% of the annual runoff volume.
- Outlet designed to discharge the capture volume over a period of hours.
- Length to width ratio of at least 1.5:1 where feasible.
- Basin depths optimally range from 2 to 5 feet.
- Include energy dissipation in the inlet design to reduce resuspension of accumulated sediment.
- A maintenance ramp and perimeter access should be included in the design to facilitate access to the basin for maintenance activities and for vector surveillance and control.
- Use a draw down time of 48 hours in most areas of California. Draw down times in excess of 48 hours may result in vector breeding, and should be used only after coordination with local vector control authorities. Draw down times of less than 48 hours should be limited to BMP drainage areas with coarse soils that readily settle and to watersheds where warming may be determined to downstream fisheries.

Construction/Inspection Considerations

- Inspect facility after first large to storm to determine whether the desired residence time has been achieved.
- When constructed with small tributary area, orifice sizing is critical and inspection should verify that flow through additional openings such as bolt holes does not occur.

Performance

One objective of stormwater management practices can be to reduce the flood hazard associated with large storm events by reducing the peak flow associated with these storms. Dry extended detention basins can easily be designed for flood control, and this is actually the primary purpose of most detention ponds.

Dry extended detention basins provide moderate pollutant removal, provided that the recommended design features are incorporated. Although they can be effective at removing

some pollutants through settling, they are less effective at removing soluble pollutants because of the absence of a permanent pool. Several studies are available on the effectiveness of dry extended detention ponds including one recently concluded by Caltrans (2002).

The load reduction is greater than the concentration reduction because of the substantial infiltration that occurs. Although the infiltration of stormwater is clearly beneficial to surface receiving waters, there is the potential for groundwater contamination. Previous research on the effects of incidental infiltration on groundwater quality indicated that the risk of contamination is minimal.

There were substantial differences in the amount of infiltration that were observed in the earthen basins during the Caltrans study. On average, approximately 40 percent of the runoff entering the unlined basins infiltrated and was not discharged. The percentage ranged from a high of about 60 percent to a low of only about 8 percent for the different facilities. Climatic conditions and local water table elevation are likely the principal causes of this difference. The least infiltration occurred at a site located on the coast where humidity is higher and the basin invert is within a few meters of sea level. Conversely, the most infiltration occurred at a facility located well inland in Los Angeles County where the climate is much warmer and the humidity is less, resulting in lower soil moisture content in the basin floor at the beginning of storms.

Vegetated detention basins appear to have greater pollutant removal than concrete basins. In the Caltrans study, the concrete basin exported sediment and associated pollutants during a number of storms. Export was not as common in the earthen basins, where the vegetation appeared to help stabilize the retained sediment.

Siting Criteria

Dry extended detention ponds are among the most widely applicable stormwater management practices and are especially useful in retrofit situations where their low hydraulic head requirements allow them to be sited within the constraints of the existing storm drain system. In addition, many communities have detention basins designed for flood control. It is possible to modify these facilities to incorporate features that provide water quality treatment and/or channel protection. Although dry extended detention ponds can be applied rather broadly, designers need to ensure that they are feasible at the site in question. This section provides basic guidelines for siting dry extended detention ponds.

In general, dry extended detention ponds should be used on sites with a minimum area of 5 acres. With this size catchment area, the orifice size can be on the order of 0.5 inches. On smaller sites, it can be challenging to provide channel or water quality control because the orifice diameter at the outlet needed to control relatively small storms becomes very small and thus prone to clogging. In addition, it is generally more cost-effective to control larger drainage areas due to the economies of scale.

Extended detention basins can be used with almost all soils and geology, with minor design adjustments for regions of rapidly percolating soils such as sand. In these areas, extended detention ponds may need an impermeable liner to prevent ground water contamination.

The base of the extended detention facility should not intersect the water table. A permanently wet bottom may become a mosquito breeding ground. Research in Southwest Florida (Santana et al., 1994) demonstrated that intermittently flooded systems, such as dry extended detention

ponds, produce more mosquitoes than other pond systems, particularly when the facilities remained wet for more than 3 days following heavy rainfall.

A study in Prince George's County, Maryland, found that stormwater management practices can increase stream temperatures (Galli, 1990). Overall, dry extended detention ponds increased temperature by about 5°F. In cold water streams, dry ponds should be designed to detain stormwater for a relatively short time (i.e., 24 hours) to minimize the amount of warming that occurs in the basin.

Additional Design Guidelines

In order to enhance the effectiveness of extended detention basins, the dimensions of the basin must be sized appropriately. Merely providing the required storage volume will not ensure maximum constituent removal. By effectively configuring the basin, the designer will create a long flow path, promote the establishment of low velocities, and avoid having stagnant areas of the basin. To promote settling and to attain an appealing environment, the design of the basin should consider the length to width ratio, cross-sectional areas, basin slopes and pond configuration, and aesthetics (Young et al., 1996).

Energy dissipation structures should be included for the basin inlet to prevent resuspension of accumulated sediment. The use of stilling basins for this purpose should be avoided because the standing water provides a breeding area for mosquitoes.

Extended detention facilities should be sized to completely capture the water quality volume. A micropool is often recommended for inclusion in the design and one is shown in the schematic diagram. These small permanent pools greatly increase the potential for mosquito breeding and complicate maintenance activities; consequently, they are not recommended for use in California.

A large aspect ratio may improve the performance of detention basins; consequently, the outlets should be placed to maximize the flowpath through the facility. The ratio of flowpath length to width from the inlet to the outlet should be at least 1.5:1 (L:W) where feasible. Basin depths optimally range from 2 to 5 feet.

The facility's drawdown time should be regulated by an orifice or weir. In general, the outflow structure should have a trash rack or other acceptable means of preventing clogging at the entrance to the outflow pipes. The outlet design implemented by Caltrans in the facilities constructed in San Diego County used an outlet riser with orifices sized to discharge the water quality volume, and the riser




Figure 1
Example of Extended Detention Outlet Structure

overflow height was set to the design storm elevation. A stainless steel screen was placed

around the outlet riser to ensure that the orifices would not become clogged with debris. Sites either used a separate riser or broad crested weir for overflow of runoff for the 25 and greater year storms. A picture of a typical outlet is presented in Figure 1.

The outflow structure should be sized to allow for complete drawdown of the water quality volume in 72 hours. No more than 50% of the water quality volume should drain from the facility within the first 24 hours. The outflow structure can be fitted with a valve so that discharge from the basin can be halted in case of an accidental spill in the watershed.

Summary of Design Recommendations

- (1) **Facility Sizing** - The required water quality volume is determined by local regulations or the basin should be sized to capture and treat 85% of the annual runoff volume. See Section 5.5.1 of the handbook for a discussion of volume-based design.

Basin Configuration – A high aspect ratio may improve the performance of detention basins; consequently, the outlets should be placed to maximize the flowpath through the facility. The ratio of flowpath length to width from the inlet to the outlet should be at least 1.5:1 (L:W). The flowpath length is defined as the distance from the inlet to the outlet as measured at the surface. The width is defined as the mean width of the basin. Basin depths optimally range from 2 to 5 feet. The basin may include a sediment forebay to provide the opportunity for larger particles to settle out.

A micropool should not be incorporated in the design because of vector concerns. For online facilities, the principal and emergency spillways must be sized to provide 1.0 foot of freeboard during the 25-year event and to safely pass the flow from 100-year storm.
- (2) **Pond Side Slopes** - Side slopes of the pond should be 3:1 (H:V) or flatter for grass stabilized slopes. Slopes steeper than 3:1 (H:V) must be stabilized with an appropriate slope stabilization practice.
- (3) **Basin Lining** – Basins must be constructed to prevent possible contamination of groundwater below the facility.
- (4) **Basin Inlet** – Energy dissipation is required at the basin inlet to reduce resuspension of accumulated sediment and to reduce the tendency for short-circuiting.
- (5) **Outflow Structure** - The facility's drawdown time should be regulated by a gate valve or orifice plate. In general, the outflow structure should have a trash rack or other acceptable means of preventing clogging at the entrance to the outflow pipes.

The outflow structure should be sized to allow for complete drawdown of the water quality volume in 72 hours. No more than 50% of the water quality volume should drain from the facility within the first 24 hours. The outflow structure should be fitted with a valve so that discharge from the basin can be halted in case of an accidental spill in the watershed. This same valve also can be used to regulate the rate of discharge from the basin.

The discharge through a control orifice is calculated from:

$$Q = CA(2gH - H_o)^{0.5}$$

where: Q = discharge (ft³/s)
 C = orifice coefficient
 A = area of the orifice (ft²)
 g = gravitational constant (32.2)
 H = water surface elevation (ft)
 H_o = orifice elevation (ft)

Recommended values for C are 0.66 for thin materials and 0.80 when the material is thicker than the orifice diameter. This equation can be implemented in spreadsheet form with the pond stage/volume relationship to calculate drain time. To do this, use the initial height of the water above the orifice for the water quality volume. Calculate the discharge and assume that it remains constant for approximately 10 minutes. Based on that discharge, estimate the total discharge during that interval and the new elevation based on the stage volume relationship. Continue to iterate until H is approximately equal to H_o. When using multiple orifices the discharge from each is summed.

- (6) Splitter Box - When the pond is designed as an offline facility, a splitter structure is used to isolate the water quality volume. The splitter box, or other flow diverting approach, should be designed to convey the 25-year storm event while providing at least 1.0 foot of freeboard along pond side slopes.
- (7) Erosion Protection at the Outfall - For online facilities, special consideration should be given to the facility's outfall location. Flared pipe end sections that discharge at or near the stream invert are preferred. The channel immediately below the pond outfall should be modified to conform to natural dimensions, and lined with large stone riprap placed over filter cloth. Energy dissipation may be required to reduce flow velocities from the primary spillway to non-erosive velocities.
- (8) Safety Considerations - Safety is provided either by fencing of the facility or by managing the contours of the pond to eliminate dropoffs and other hazards. Earthen side slopes should not exceed 3:1 (H:V) and should terminate on a flat safety bench area. Landscaping can be used to impede access to the facility. The primary spillway opening must not permit access by small children. Outfall pipes above 48 inches in diameter should be fenced.

Maintenance

Routine maintenance activity is often thought to consist mostly of sediment and trash and debris removal; however, these activities often constitute only a small fraction of the maintenance hours. During a recent study by Caltrans, 72 hours of maintenance was performed annually, but only a little over 7 hours was spent on sediment and trash removal. The largest recurring activity was vegetation management, routine mowing. The largest absolute number of hours was associated with vector control because of mosquito breeding that occurred in the stilling basins (example of standing water to be avoided) installed as energy dissipaters. In most cases, basic housekeeping practices such as removal of debris accumulations and vegetation management to ensure that the basin dewater completely in 48-72 hours is sufficient to prevent creating mosquito and other vector habitats.

Consequently, maintenance costs should be estimated based primarily on the mowing frequency and the time required. Mowing should be done at least annually to avoid establishment of woody vegetation, but may need to be performed much more frequently if aesthetics are an important consideration.

Typical activities and frequencies include:

- Schedule semiannual inspection for the beginning and end of the wet season for standing water, slope stability, sediment accumulation, trash and debris, and presence of burrows.
- Remove accumulated trash and debris in the basin and around the riser pipe during the semiannual inspections. The frequency of this activity may be altered to meet specific site conditions.
- Trim vegetation at the beginning and end of the wet season and inspect monthly to prevent establishment of woody vegetation and for aesthetic and vector reasons.
- Remove accumulated sediment and regrade about every 10 years or when the accumulated sediment volume exceeds 10 percent of the basin volume. Inspect the basin each year for accumulated sediment volume.

Cost

Construction Cost

The construction costs associated with extended detention basins vary considerably. One recent study evaluated the cost of all pond systems (Brown and Schueler, 1997). Adjusting for inflation, the cost of dry extended detention ponds can be estimated with the equation:

$$C = 12.4V^{0.760}$$

where: C = Construction, design, and permitting cost, and
V = Volume (ft³).

Using this equation, typical construction costs are:

\$ 41,600 for a 1 acre-foot pond

\$ 239,000 for a 10 acre-foot pond

\$ 1,380,000 for a 100 acre-foot pond

Interestingly, these costs are generally slightly higher than the predicted cost of wet ponds (according to Brown and Schueler, 1997) on a cost per total volume basis, which highlights the difficulty of developing reasonably accurate construction estimates. In addition, a typical facility constructed by Caltrans cost about \$160,000 with a capture volume of only 0.3 ac-ft.

An economic concern associated with dry ponds is that they might detract slightly from the value of adjacent properties. One study found that dry ponds can actually detract from the perceived value of homes adjacent to a dry pond by between 3 and 10 percent (Emmerling-Dinovo, 1995).

Maintenance Cost

For ponds, the annual cost of routine maintenance is typically estimated at about 3 to 5 percent of the construction cost (EPA website). Alternatively, a community can estimate the cost of the maintenance activities outlined in the maintenance section. Table 1 presents the maintenance costs estimated by Caltrans based on their experience with five basins located in southern California. Again, it should be emphasized that the vast majority of hours are related to vegetation management (mowing).

Table 1 Estimated Average Annual Maintenance Effort			
Activity	Labor Hours	Equipment & Material (\$)	Cost
Inspections	4	7	183
Maintenance	49	126	2282
Vector Control	0	0	0
Administration	3	0	132
Materials	-	535	535
Total	56	\$668	\$3,132

References and Sources of Additional Information

Brown, W., and T. Schueler. 1997. *The Economics of Stormwater BMPs in the Mid-Atlantic Region*. Prepared for Chesapeake Research Consortium. Edgewater, MD. Center for Watershed Protection. Ellicott City, MD.

Denver Urban Drainage and Flood Control District. 1992. *Urban Storm Drainage Criteria Manual—Volume 3: Best Management Practices*. Denver, CO.

Emmerling-Dinovo, C. 1995. Stormwater Detention Basins and Residential Locational Decisions. *Water Resources Bulletin* 31(3): 515–521

Galli, J. 1990. *Thermal Impacts Associated with Urbanization and Stormwater Management Best Management Practices*. Metropolitan Washington Council of Governments. Prepared for Maryland Department of the Environment, Baltimore, MD.

GKY, 1989, *Outlet Hydraulics of Extended Detention Facilities* for the Northern Virginia Planning District Commission.

MacRae, C. 1996. Experience from Morphological Research on Canadian Streams: Is Control of the Two-Year Frequency Runoff Event the Best Basis for Stream Channel Protection? In *Effects of Watershed Development and Management on Aquatic Ecosystems*. American Society of Civil Engineers. Edited by L. Roesner. Snowbird, UT. pp. 144–162.

Maryland Dept of the Environment, 2000, *Maryland Stormwater Design Manual: Volumes 1 & 2*, prepared by MDE and Center for Watershed Protection.

<http://www.mde.state.md.us/environment/wma/stormwatermanual/index.html>

Metzger, M. E., D. F. Messer, C. L. Beitia, C. M. Myers, and V. L. Kramer. 2002. The Dark Side Of Stormwater Runoff Management: Disease Vectors Associated With Structural BMPs. *Stormwater* 3(2): 24-39.

Santana, F., J. Wood, R. Parsons, and S. Chamberlain. 1994. Control of Mosquito Breeding in Permitted Stormwater Systems. Prepared for Southwest Florida Water Management District, Brooksville, FL.

Schueler, T. 1997. Influence of Ground Water on Performance of Stormwater Ponds in Florida. *Watershed Protection Techniques* 2(4):525-528.

Watershed Management Institute (WMI). 1997. *Operation, Maintenance, and Management of Stormwater Management Systems*. Prepared for U.S. Environmental Protection Agency, Office of Water, Washington, DC.


Young, G.K., et al., 1996, *Evaluation and Management of Highway Runoff Water Quality*, Publication No. FHWA-PD-96-032, U.S. Department of Transportation, Federal Highway Administration, Office of Environment and Planning.

Information Resources


Center for Watershed Protection (CWP), Environmental Quality Resources, and Loiederman Associates. 1997. *Maryland Stormwater Design Manual*. Draft. Prepared for Maryland Department of the Environment, Baltimore, MD.

Center for Watershed Protection (CWP). 1997. *Stormwater BMP Design Supplement for Cold Climates*. Prepared for U.S. Environmental Protection Agency, Office of Wetlands, Oceans and Watersheds, Washington, DC.

U.S. Environmental Protection Agency (USEPA). 1993. *Guidance Specifying Management Measures for Sources of Nonpoint Pollution in Coastal Waters*. EPA-840-B-92-002. U.S. Environmental Protection Agency, Office of Water, Washington, DC.



PLAN VIEW



PROFILE

Schematic of an Extended Detention Basin (MDE, 2000)



Design Considerations

- Soil for Infiltration
- Tributary Area
- Slope
- Aesthetics
- Environmental Side-effects

Description

The bioretention best management practice (BMP) functions as a soil and plant-based filtration device that removes pollutants through a variety of physical, biological, and chemical treatment processes. These facilities normally consist of a grass buffer strip, sand bed, ponding area, organic layer or mulch layer, planting soil, and plants. The runoff's velocity is reduced by passing over or through buffer strip and subsequently distributed evenly along a ponding area. Exfiltration of the stored water in the bioretention area planting soil into the underlying soils occurs over a period of days.

California Experience

None documented. Bioretention has been used as a stormwater BMP since 1992. In addition to Prince George's County, MD and Alexandria, VA, bioretention has been used successfully at urban and suburban areas in Montgomery County, MD; Baltimore County, MD; Chesterfield County, VA; Prince William County, VA; Smith Mountain Lake State Park, VA; and Cary, NC.

Advantages

- Bioretention provides stormwater treatment that enhances the quality of downstream water bodies by temporarily storing runoff in the BMP and releasing it over a period of four days to the receiving water (EPA, 1999).
- The vegetation provides shade and wind breaks, absorbs noise, and improves an area's landscape.

Limitations

- The bioretention BMP is not recommended for areas with slopes greater than 20% or where mature tree removal would

Targeted Constituents

✓ Sediment	■
✓ Nutrients	▲
✓ Trash	■
✓ Metals	■
✓ Bacteria	■
✓ Oil and Grease	■
✓ Organics	■

Legend (Removal Effectiveness)

- Low
- High
- ▲ Medium



be required since clogging may result, particularly if the BMP receives runoff with high sediment loads (EPA, 1999).

- Bioretention is not a suitable BMP at locations where the water table is within 6 feet of the ground surface and where the surrounding soil stratum is unstable.
- By design, bioretention BMPs have the potential to create very attractive habitats for mosquitoes and other vectors because of highly organic, often heavily vegetated areas mixed with shallow water.
- In cold climates the soil may freeze, preventing runoff from infiltrating into the planting soil.

Design and Sizing Guidelines

- The bioretention area should be sized to capture the design storm runoff.
- In areas where the native soil permeability is less than 0.5 in/hr an underdrain should be provided.
- Recommended minimum dimensions are 15 feet by 40 feet, although the preferred width is 25 feet. Excavated depth should be 4 feet.
- Area should drain completely within 72 hours.
- Approximately 1 tree or shrub per 50 ft² of bioretention area should be included.
- Cover area with about 3 inches of mulch.

Construction/Inspection Considerations

Bioretention area should not be established until contributing watershed is stabilized.

Performance

Bioretention removes stormwater pollutants through physical and biological processes, including adsorption, filtration, plant uptake, microbial activity, decomposition, sedimentation and volatilization (EPA, 1999). Adsorption is the process whereby particulate pollutants attach to soil (e.g., clay) or vegetation surfaces. Adequate contact time between the surface and pollutant must be provided for in the design of the system for this removal process to occur. Thus, the infiltration rate of the soils must not exceed those specified in the design criteria or pollutant removal may decrease. Pollutants removed by adsorption include metals, phosphorus, and hydrocarbons. Filtration occurs as runoff passes through the bioretention area media, such as the sand bed, ground cover, and planting soil.

Common particulates removed from stormwater include particulate organic matter, phosphorus, and suspended solids. Biological processes that occur in wetlands result in pollutant uptake by plants and microorganisms in the soil. Plant growth is sustained by the uptake of nutrients from the soils, with woody plants locking up these nutrients through the seasons. Microbial activity within the soil also contributes to the removal of nitrogen and organic matter. Nitrogen is removed by nitrifying and denitrifying bacteria, while aerobic bacteria are responsible for the decomposition of the organic matter. Microbial processes require oxygen and can result in depleted oxygen levels if the bioretention area is not adequately

aerated. Sedimentation occurs in the swale or ponding area as the velocity slows and solids fall out of suspension.

The removal effectiveness of bioretention has been studied during field and laboratory studies conducted by the University of Maryland (Davis et al, 1998). During these experiments, synthetic stormwater runoff was pumped through several laboratory and field bioretention areas to simulate typical storm events in Prince George's County, MD. Removal rates for heavy metals and nutrients are shown in Table 1.

Pollutant	Removal Rate
Total Phosphorus	70-83%
Metals (Cu, Zn, Pb)	93-98%
TKN	68-80%
Total Suspended Solids	90%
Organics	90%
Bacteria	90%

Results for both the laboratory and field experiments were similar for each of the pollutants analyzed. Doubling or halving the influent pollutant levels had little effect on the effluent pollutants concentrations (Davis et al, 1998).

The microbial activity and plant uptake occurring in the bioretention area will likely result in higher removal rates than those determined for infiltration BMPs.

Siting Criteria

Bioretention BMPs are generally used to treat stormwater from impervious surfaces at commercial, residential, and industrial areas (EPA, 1999). Implementation of bioretention for stormwater management is ideal for median strips, parking lot islands, and swales. Moreover, the runoff in these areas can be designed to either divert directly into the bioretention area or convey into the bioretention area by a curb and gutter collection system.

The best location for bioretention areas is upland from inlets that receive sheet flow from graded areas and at areas that will be excavated (EPA, 1999). In order to maximize treatment effectiveness, the site must be graded in such a way that minimizes erosive conditions as sheet flow is conveyed to the treatment area. Locations where a bioretention area can be readily incorporated into the site plan without further environmental damage are preferred. Furthermore, to effectively minimize sediment loading in the treatment area, bioretention only should be used in stabilized drainage areas.

Additional Design Guidelines

The layout of the bioretention area is determined after site constraints such as location of utilities, underlying soils, existing vegetation, and drainage are considered (EPA, 1999). Sites with loamy sand soils are especially appropriate for bioretention because the excavated soil can be backfilled and used as the planting soil, thus eliminating the cost of importing planting soil.

The use of bioretention may not be feasible given an unstable surrounding soil stratum, soils with clay content greater than 25 percent, a site with slopes greater than 20 percent, and/or a site with mature trees that would be removed during construction of the BMP.

Bioretention can be designed to be off-line or on-line of the existing drainage system (EPA, 1999). The drainage area for a bioretention area should be between 0.1 and 0.4 hectares (0.25 and 1.0 acres). Larger drainage areas may require multiple bioretention areas. Furthermore, the maximum drainage area for a bioretention area is determined by the expected rainfall intensity and runoff rate. Stabilized areas may erode when velocities are greater than 5 feet per second (1.5 meter per second). The designer should determine the potential for erosive conditions at the site.

The size of the bioretention area, which is a function of the drainage area and the runoff generated from the area is sized to capture the water quality volume.

The recommended minimum dimensions of the bioretention area are 15 feet (4.6 meters) wide by 40 feet (12.2 meters) long, where the minimum width allows enough space for a dense, randomly-distributed area of trees and shrubs to become established. Thus replicating a natural forest and creating a microclimate, thereby enabling the bioretention area to tolerate the effects of heat stress, acid rain, runoff pollutants, and insect and disease infestations which landscaped areas in urban settings typically are unable to tolerate. The preferred width is 25 feet (7.6 meters), with a length of twice the width. Essentially, any facilities wider than 20 feet (6.1 meters) should be twice as long as they are wide, which promotes the distribution of flow and decreases the chances of concentrated flow.

In order to provide adequate storage and prevent water from standing for excessive periods of time the ponding depth of the bioretention area should not exceed 6 inches (15 centimeters). Water should not be left to stand for more than 72 hours. A restriction on the type of plants that can be used may be necessary due to some plants' water intolerance. Furthermore, if water is left standing for longer than 72 hours mosquitoes and other insects may start to breed.

The appropriate planting soil should be backfilled into the excavated bioretention area. Planting soils should be sandy loam, loamy sand, or loam texture with a clay content ranging from 10 to 25 percent.

Generally the soil should have infiltration rates greater than 0.5 inches (1.25 centimeters) per hour, which is typical of sandy loams, loamy sands, or loams. The pH of the soil should range between 5.5 and 6.5, where pollutants such as organic nitrogen and phosphorus can be adsorbed by the soil and microbial activity can flourish. Additional requirements for the planting soil include a 1.5 to 3 percent organic content and a maximum 500 ppm concentration of soluble salts.

Soil tests should be performed for every 500 cubic yards (382 cubic meters) of planting soil, with the exception of pH and organic content tests, which are required only once per bioretention area (EPA, 1999). Planting soil should be 4 inches (10.1 centimeters) deeper than the bottom of the largest root ball and 4 feet (1.2 meters) altogether. This depth will provide adequate soil for the plants' root systems to become established, prevent plant damage due to severe wind, and provide adequate moisture capacity. Most sites will require excavation in order to obtain the recommended depth.

Planting soil depths of greater than 4 feet (1.2 meters) may require additional construction practices such as shoring measures (EPA, 1999). Planting soil should be placed in 18 inches or greater lifts and lightly compacted until the desired depth is reached. Since high canopy trees may be destroyed during maintenance the bioretention area should be vegetated to resemble a terrestrial forest community ecosystem that is dominated by understory trees. Three species each of both trees and shrubs are recommended to be planted at a rate of 2500 trees and shrubs per hectare (1000 per acre). For instance, a 15 foot (4.6 meter) by 40 foot (12.2 meter) bioretention area (600 square feet or 55.75 square meters) would require 14 trees and shrubs. The shrub-to-tree ratio should be 2:1 to 3:1.

Trees and shrubs should be planted when conditions are favorable. Vegetation should be watered at the end of each day for fourteen days following its planting. Plant species tolerant of pollutant loads and varying wet and dry conditions should be used in the bioretention area.

The designer should assess aesthetics, site layout, and maintenance requirements when selecting plant species. Adjacent non-native invasive species should be identified and the designer should take measures, such as providing a soil breach to eliminate the threat of these species invading the bioretention area. Regional landscaping manuals should be consulted to ensure that the planting of the bioretention area meets the landscaping requirements established by the local authorities. The designers should evaluate the best placement of vegetation within the bioretention area. Plants should be placed at irregular intervals to replicate a natural forest. Trees should be placed on the perimeter of the area to provide shade and shelter from the wind. Trees and shrubs can be sheltered from damaging flows if they are placed away from the path of the incoming runoff. In cold climates, species that are more tolerant to cold winds, such as evergreens, should be placed in windier areas of the site.

Following placement of the trees and shrubs, the ground cover and/or mulch should be established. Ground cover such as grasses or legumes can be planted at the beginning of the growing season. Mulch should be placed immediately after trees and shrubs are planted. Two to 3 inches (5 to 7.6 cm) of commercially-available fine shredded hardwood mulch or shredded hardwood chips should be applied to the bioretention area to protect from erosion.

Maintenance

The primary maintenance requirement for bioretention areas is that of inspection and repair or replacement of the treatment area's components. Generally, this involves nothing more than the routine periodic maintenance that is required of any landscaped area. Plants that are appropriate for the site, climatic, and watering conditions should be selected for use in the bioretention cell. Appropriately selected plants will aid in reducing fertilizer, pesticide, water, and overall maintenance requirements. Bioretention system components should blend over time through plant and root growth, organic decomposition, and the development of a natural

soil horizon. These biologic and physical processes over time will lengthen the facility's life span and reduce the need for extensive maintenance.

Routine maintenance should include a biannual health evaluation of the trees and shrubs and subsequent removal of any dead or diseased vegetation (EPA, 1999). Diseased vegetation should be treated as needed using preventative and low-toxic measures to the extent possible. BMPs have the potential to create very attractive habitats for mosquitoes and other vectors because of highly organic, often heavily vegetated areas mixed with shallow water. Routine inspections for areas of standing water within the BMP and corrective measures to restore proper infiltration rates are necessary to prevent creating mosquito and other vector habitat. In addition, bioretention BMPs are susceptible to invasion by aggressive plant species such as cattails, which increase the chances of water standing and subsequent vector production if not routinely maintained.

In order to maintain the treatment area's appearance it may be necessary to prune and weed. Furthermore, mulch replacement is suggested when erosion is evident or when the site begins to look unattractive. Specifically, the entire area may require mulch replacement every two to three years, although spot mulching may be sufficient when there are random void areas. Mulch replacement should be done prior to the start of the wet season.

New Jersey's Department of Environmental Protection states in their bioretention systems standards that accumulated sediment and debris removal (especially at the inflow point) will normally be the primary maintenance function. Other potential tasks include replacement of dead vegetation, soil pH regulation, erosion repair at inflow points, mulch replenishment, unclogging the underdrain, and repairing overflow structures. There is also the possibility that the cation exchange capacity of the soils in the cell will be significantly reduced over time. Depending on pollutant loads, soils may need to be replaced within 5-10 years of construction (LID, 2000).

Cost

Construction Cost

Construction cost estimates for a bioretention area are slightly greater than those for the required landscaping for a new development (EPA, 1999). A general rule of thumb (Coffman, 1999) is that residential bioretention areas average about \$3 to \$4 per square foot, depending on soil conditions and the density and types of plants used. Commercial, industrial and institutional site costs can range between \$10 to \$40 per square foot, based on the need for control structures, curbing, storm drains and underdrains.

Retrofitting a site typically costs more, averaging \$6,500 per bioretention area. The higher costs are attributed to the demolition of existing concrete, asphalt, and existing structures and the replacement of fill material with planting soil. The costs of retrofitting a commercial site in Maryland, Kettering Development, with 15 bioretention areas were estimated at \$111,600.

In any bioretention area design, the cost of plants varies substantially and can account for a significant portion of the expenditures. While these cost estimates are slightly greater than those of typical landscaping treatment (due to the increased number of plantings, additional soil excavation, backfill material, use of underdrains etc.), those landscaping expenses that would be required regardless of the bioretention installation should be subtracted when determining the net cost.

Perhaps of most importance, however, the cost savings compared to the use of traditional structural stormwater conveyance systems makes bioretention areas quite attractive financially. For example, the use of bioretention can decrease the cost required for constructing stormwater conveyance systems at a site. A medical office building in Maryland was able to reduce the amount of storm drain pipe that was needed from 800 to 230 feet - a cost savings of \$24,000 (PGDER, 1993). And a new residential development spent a total of approximately \$100,000 using bioretention cells on each lot instead of nearly \$400,000 for the traditional stormwater ponds that were originally planned (Rappahanock,). Also, in residential areas, stormwater management controls become a part of each property owner's landscape, reducing the public burden to maintain large centralized facilities.

Maintenance Cost

The operation and maintenance costs for a bioretention facility will be comparable to those of typical landscaping required for a site. Costs beyond the normal landscaping fees will include the cost for testing the soils and may include costs for a sand bed and planting soil.

References and Sources of Additional Information

Coffman, L.S., R. Goo and R. Frederick, 1999: Low impact development: an innovative alternative approach to stormwater management. Proceedings of the 26th Annual Water Resources Planning and Management Conference ASCE, June 6-9, Tempe, Arizona.

Davis, A.P., Shokouhian, M., Sharma, H. and Minami, C., "Laboratory Study of Biological Retention (Bioretention) for Urban Stormwater Management," *Water Environ. Res.*, 73(1), 5-14 (2001).

Davis, A.P., Shokouhian, M., Sharma, H., Minami, C., and Winogradoff, D. "Water Quality Improvement through Bioretention: Lead, Copper, and Zinc," *Water Environ. Res.*, accepted for publication, August 2002.


Kim, H., Seagren, E.A., and Davis, A.P., "Engineered Bioretention for Removal of Nitrate from Stormwater Runoff," *WEFTEC 2000 Conference Proceedings on CDROM Research Symposium, Nitrogen Removal*, Session 19, Anaheim CA, October 2000.

Hsieh, C.-h. and Davis, A.P. "Engineering Bioretention for Treatment of Urban Stormwater Runoff," *Watersheds 2002, Proceedings on CDROM Research Symposium*, Session 15, Ft. Lauderdale, FL, Feb. 2002.


Prince George's County Department of Environmental Resources (PGDER), 1993. Design Manual for Use of *Bioretention in Stormwater Management*. Division of Environmental Management, Watershed Protection Branch. Landover, MD.

U.S. EPA Office of Water, 1999. Stormwater Technology Fact Sheet: Bioretention. EPA 832-F-99-012.

Weinstein, N. Davis, A.P. and Veeramachaneni, R. "Low Impact Development (LID) Stormwater Management Approach for the Control of Diffuse Pollution from Urban Roadways," *5th International Conference Diffuse/Nonpoint Pollution and Watershed Management Proceedings*, C.S. Melching and Emre Alp, Eds. 2001 International Water Association



PLAN VIEW



PROFILE

Schematic of a Bioretention Facility (MDE, 2000)

Nutrient Separating Baffle Box

A Superior Stormwater Treatment System Separated from the Rest.

The Nutrient Separating Baffle Box (NSBB) is a widely accepted and desired stormwater solution chosen by civil engineers, municipalities and developers nationwide because of its superior characteristics. The NSBB is easy to install and maintain and is the only systems with a two stage maintenance option, which minimizes maintenance costs.

Hundreds of Nutrient Separating Baffle Boxes have been installed nation wide, from Florida to California because of its superior and proven design. The NSBB efficiently removes TSS, hydrocarbons, nutrients, metals and debris/organics from stormwater runoff. The patented filtration screen system captures and stores trash and organics in a dry state, which prevents nutrient leaching and bacterial build up.


System Characteristics

Traps Oil & Grease
The skimmer and hydrocarbon booms captures all forms of hydrocarbons.

High TSS Removal
The three chambered design maximizes capture of large and fine TSS.

89.8% TSS Removal
Pantit - 1996
86.3% TSS Removal
Honey Lake - 2004
93.3% TSS Removal
Dillard - 2006

Low Installation Cost
Bottom of structure less than 4 feet from invert of pipe.



NJ CAT VERIFIED

Separates Nutrients & Trash
The patented filtration screen system captures and stores trash and organics in a dry state which prevents nutrient

Low Head Loss
Allows for easy retrofit and inline installation. Eliminates the need for expensive diversion structures.

Easy Maintenance
Unobstructed Manhole Access

POLLUTANT	REMOVAL EFFICIENCY
Trash & Debris	99% ¹
TSS	76.9% ² to 93.3% ³
Fine TSS (d ₅₀ 63 µm)	67.3% ⁴
Metals	Up to 57% ⁵
Total Nitrogen	38% to 63% ⁵
Total Phosphorus	18% to 70% ^{2,5}

¹ Backlogge Baffle Box Independent Field Report, San and Environmental Technology, 2007
² Dillard Center, Meira & Associates 7 St. Johns River Water Management District, 1994
³ First Test for Stormwater Nutrient Separating Baffle Box, Dillard & Associates, 2006
⁴ New Jersey Commission for Technical Training, 2008
⁵ Science Based Field Report, Blue Water Technology, 2004

Setting a New Standard for Hydrodynamic Separators.

The Nutrient Separating Baffle Box is designed to do more than most systems. This system is effective at removing not only TSS, but also fine TSS and gross solids making it, overall, a more effective treatment system compared to traditional swirl type separators. This system has been proven to provide the following benefits:


System Benefits


- **Can Treat 100% of the Flow.**
Offline Configuration is Not Required.
- **Inexpensive Maintenance.**
Patented screen system allows gross solids to be removed without vacuuming out the water.
- **Minimal Head Loss.**
Hydraulically efficient design generates less head loss than diversion structures.
- **Custom Designs Available.**
Can be modified to meet your needs.
- **Easy to Install.**
Delivered in a top & bottom half to minimize weight. Shallow profile minimizes installation costs.
- **5 Year Warranty.**
Made of precast concrete, fiberglass, aluminum & stainless steel. No cheap plastics!

Functional Description

Captures:

- Trash & Debris 
- Oxygen Demanding Substances/Organic Compounds 
- Hydrocarbons, Oils & Grease
- TSS (including fines)
- Nutrients (particulates)
- Heavy Metals (particulates)

"Pollutants with this symbol  are stored in a dry state".




During Storm Event

Why Dry State Storage?

Storing Trash, Debris, Organics, and Oxygen Demanding Substances in a Dry State Prevents:

- Prevent Nutrient Leaching
- Eliminate Septic Conditions
- Minimize Bacteria Growth
- Eliminate Bad Odors

Nutrient Separating Baffle Box




Standing Water is Clear & No Bacteria Growth Visible.

Other Systems



Standing Water is Not Clear & Bacteria Growth Visible.



Operation:

Skimmer & Boom

Collects hydrocarbons & controls flow velocity which improves removal efficiency.

Deflectors

Prevents re-suspension of captured pollutants at higher flows by directing water currents above sediment chambers.

Filtration Screen System

Collects and stores trash, debris, organics, and oxygen demanding substances in a dry state above the standing water. As mentioned above this has many performance benefits along with simplifying maintenance.

Multiple Sediment Chambers

Maximizes TSS removal and eliminates scouring during extreme flow rates.

MWS-LINEAR 2.0 STORMWATER FILTRATION SYSTEM

NATURE AND TECHNOLOGY WORKING TOGETHER IN PERFECT HARMONY.

The need for a new stormwater treatment system is evident. Federal and state requirements on cities and industry to reduce stormwater runoff increase every year as our population explodes. The EPA is now reporting that stormwater runoff represents the nation's number one water quality problem, and is the reason why nearly half of our rivers and lakes are not even clean enough to support fishing or swimming. *Nearly half.*



To combat this catastrophe, we turned to the expert in this field: **Nature**. By developing technology that imitates the processes found in nature, we've created the most advanced stormwater filtration system available. Years ahead of current EPA requirements, our clients understand that when they invest in our new technology, they are investing in the future. For all of us.



GRATE TYPE



CURB TYPE

MWS-LINEAR TESTED REMOVAL EFFICIENCIES


TSS	Nitrate	Copper	Zinc	Oils & Grease	Bacteria	Turbidity
82% - 98%	74%	>53% - 93%	79% - 81%	84% - 99%	60% - 89%	>90%

Washington State
DOE Approved

SIZING


Model #	Dimensions (ft)	WetlandMedia Surface Area (sq ft)	Treatment Flow Rate (cfs)
MWS-L-3-6	3 x 6	34	0.076
MWS-L-4-8	4 x 8	50	0.116
MWS-L-4-13	4 x 13	63	0.144
MWS-L-4-15	4 x 15	76	0.175
MWS-L-4-17	4 x 17	90	0.206
MWS-L-4-19	4 x 19	103	0.236
MWS-L-4-21	4 x 21	117	0.267

VOLUME SIZING



The Modular Wetland System is the only biofilter that can be installed downstream of detention systems.

SYSTEM OPERATIONS



FEATURES

- 1 **PRE-TREATMENT CHAMBER**
Captures incoming runoff and contains the first three stages of treatment.
- 2 **GRATE TYPE CATCH BASIN INLET**
A standard 41" x 24" grate type traffic rated catch basin opening directs stormwater into the system.
- 3 **CATCH BASIN INSERT FILTER**
Provides the first stage of treatment by capturing trash & litter, gross solids, and sediment.
- 4 **SETTLING CHAMBER**
Provides the second stage of treatment by separating out larger suspended solids.
- 5 **PRE-FILTER CARTRIDGE**
Provides the third stage of treatment by physically and chemically capturing fine TSS, metals, nutrients, and bacteria.
- 6 **WETLAND CHAMBER**
Provides the final stage of treatment through a combination of physical, chemical and biological processes.
- 7 **DISCHARGE CHAMBER**
Contains flow control, high flow bypass and optional drain down filter.
- 8 **MULTI-LEVEL FLOW CONTROL**
Orifice plates and/or valves are used to control the flow through the treatment stages.



T 760.433.7640 E info@modularwetlands.com www.modularwetlands.com

© 2012, Modular Wetlands Systems, Inc. All rights reserved. All names, trademarks and system renderings are property of Modular Wetlands Systems, Inc.

Modular Wetland Systems, Inc.

- [Home](#)
- [Products](#)
- [About](#)
- [Pollution](#)
- [Press](#)
- [Contact](#)

- [Design](#)
- [Sizing](#)
- [Drawings](#)
- [Hydraulics](#)
- [Performance](#)
- [Installation](#)
- [Maintenance](#)
- [Project Profiles](#)
- [Plant Selection](#)

Performance & Reports

The Modular Wetland System - Linear is the industry's first hybrid treatment system. It is a self-contained treatment train that incorporates the following treatment processes: screening, hydrodynamic separation, media filtration, and a bioretention filter. The bioretention filter is an enhanced sub surface flow vegetated wetland with a special blend of sorptive media. This treatment train approach makes this system very effective at removing a wide range of stormwater pollutants.

Pollutant Removal Performance

(bench scale testing)

Pollutant	Efficiency %
TSS (Sil-Co-Sil 106) (mean particle size 20 microns)	98%
Dissolved Phosphorus	22%
Dissolved Copper	93%
Dissolved Lead	81%
Dissolved Zinc	80%
Oils & Grease	84%
Total Petroleum Hydrocarbons	100%
Turbidity	93%
Fecal Coliform	66%
E. Coli	60%

Download Performance Summary

(full scale field testing)

Pollutant	Efficiency %
TSS (Sil-Co-Sil 106) (less than 15 microns)	82%
Nitrate-N	76%
Copper	53%
Lead (not present)	N/A
Zinc	79%
TPH - diesel	100%
TPH - motor oil	100%
Enterococci	70%
Fecal Coliform	84%
E. Coli	79%

More Information

For more information on performance please email us at assistance@modularwetlands.com or call 760-433-7640.

Learn More About ...



The revolutionary filter media

Copyright © 2012 Modular Wetland Systems, Inc.. All rights reserved.



Modular Wetland Systems, Inc.

- [Home](#)
- [Products](#)
- [About](#)
- [Pollution](#)
- [Press](#)
- [Contact](#)

- [Design](#)
- [Sizing](#)
- [Drawings](#)
- [Hydraulics](#)
- [Performance](#)
- [Installation](#)
- [Maintenance](#)
- [Project Profiles](#)
- [Plant Selection](#)

Performance & Reports

The Modular Wetland System - Linear is the industry's first hybrid treatment system. It is a self-contained treatment train that incorporates the following treatment processes: screening, hydrodynamic separation, media filtration, and a bioretention filter. The bioretention filter is an enhanced sub surface flow vegetated wetland with a special blend of sorptive media. This treatment train approach makes this system very effective at removing a wide range of stormwater pollutants.

Pollutant Removal Performance

(bench scale testing)

Pollutant	Efficiency %
TSS (Sil-Co-Sil 106) (mean particle size 20 microns)	98%
Dissolved Phosphorus	22%
Dissolved Copper	93%
Dissolved Lead	81%
Dissolved Zinc	80%
Oils & Grease	84%
Total Petroleum Hydrocarbons	100%
Turbidity	93%
Fecal Coliform	66%
E. Coli	60%

Download Performance Summary

(full scale field testing)

Pollutant	Efficiency %
TSS (Sil-Co-Sil 106) (less than 15 microns)	82%
Nitrate-N	76%
Copper	53%
Lead (not present)	N/A
Zinc	79%
TPH - diesel	100%
TPH - motor oil	100%
Enterococci	70%
Fecal Coliform	84%
E. Coli	79%

More Information

For more information on performance please email us at assistance@modularwetlands.com or call 760-433-7640.

Learn More About ...



The revolutionary filter media

Copyright © 2012 Modular Wetland Systems, Inc.. All rights reserved.



MWS - LINEAR

Pollutant Removal Performance Summary

Test Run	pH		TSS (mg/L)		Dissolved Phosphorus (mg/L)		Dissolved Cadmium (mg/L)		Dissolved Copper (mg/L)		Dissolved Lead (mg/L)		Dissolved Mercury (mg/L)	
	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent
	1	7.26	7.68	270	6	0.68	0.12	0.61	0.02	0.757	0.028	0.543	0.1	0.018
2	7.26	7.43	270	3	0.68	0.65	0.61	0.07	0.757	0.055	0.543	0.1	0.018	0.002
3	7.26	7.35	270	2	0.68	0.77	0.61	0.2	0.757	0.066	0.543	0.1	0.018	0.002
4	7.26	7.36	270	1	0.68	0.58	0.61	0.33	0.757	0.072	0.543	0.1	0.018	0.002
5														
6														
7														
8														
Averages	7.26	7.455	270	3	0.68	0.53	0.61	0.155	0.757	0.05525	0.543	0.1	0.018	0.002
Average Removal Efficiency (%)			98.89%		22.06%		74.59%		92.70%		81.58%		88.89%	

Using Si-Co-Sil 106

Mean particle size = 19 microns

Test Run	Dissolved Nickel (mg/L)		Dissolved Zinc (mg/L)		Oil & Grease (mg/L)		TPH (mg/L)		Turbidity (NTU)		Fecal Coliform (MPN/100 mL)		E.Coli (MPN/100 mL)	
	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent	Influent	Effluent
	1	0.37	0.01	0.95	0.05	10	1	19	0	21	0.5			
2	0.37	0.25	0.95	0.05	10	1	19	0	21	1.5				
3	0.37	0.3	0.95	0.21	10	2.5	19	0	21	1.5				
4	0.37	0.34	0.95	0.43	10	2	19	0	21	2.8				
5														
6											1600	170	1600	110
7											1600	900	1600	900
8											1600	900	1600	900
Averages	0.37	0.225	0.95	0.185	10	1.625	19	0	21	1.575	1600	535	1600	636.6667
Average Removal Efficiency (%)		39.19%		80.53%		83.75%		100.00%		92.50%		66.56%		60.21%

Red text indicates concentrations are greater than testing limits of 1600 MPN/100mL.

Testing of Quarter Scale Model - at Flow Rate of 1.9 GPM. This flow rate is equal to 121.6 GPM for full size system.

Modular Wetland System - Linear is manufactured by Modular Wetland Systems, Inc. 760-433-7640 www.modularwetlands.com

